



		尺寸公差(mm)				
		0	>30	>60	>100	0.05/10
		~30	~60	~100	~150	IT7
Rated current	16A	±0.20 ±0.30 ±0.50 ±0.70 ±1.00				
Rated voltage	300V					
Coil/Contact dielectric voltage	4000V/S					
Dielectric voltage between contact	2500V/S					
Screw torque	1.2Nm					
External connection wire	20-14/0.5-2.5W					
Ambient temperature	G/mm ²					
Key controlled symbol	-40~+85℃					*
Conform to RoHS						

Printing for laser marking/printing content is clear ,no broken line/rect
Seal literal reference according to the foot position in the drawing

REV	ECN	DESCRIPTION	DRAFT	DATE

1	DPTF08A-E3-00A(H)-N	30019000036	1		
MATERIAL: /		SURFACE: /			
MATERIAL NO.:		30020000055			
STATUS:		/			
APPD:		/			
CHKD:		/			
DRAFT:		/			
DRAWING NO.:		30000363			
TYPE:		PRODUCT DRAWING			
SCALE:		1:1			
REV	TO-1				
	1/1				

DEGSON
 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD

Description:
DPTF08A-E3-00A(H)

1 2 3 4 5 6

D

C

B

A